

HIGH BAY & LOW BAY



Brief Specification :-

CRI : >70

Power Factor : >0.90

Surge Voltage Protection : 2.5 - 10 KV

THD : <15%

IP Rating : IP65 Lifetime : 50 ,000 Hrs

| Product Code | Wattage | Lumens | CCT | Beam Angle | Body Type | Size in mm | Packing |
|---------------|---------|--------|-------|------------|-----------|------------|---------|
| LUA5 70 3000 | 70 | 7700 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 70 4000 | 70 | 8400 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 70 5700 | 70 | 8400 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 90 3000 | 90 | 10800 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 90 4000 | 90 | 10800 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 90 5700 | 90 | 10800 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 120 3000 | 120 | 13200 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 120 4000 | 120 | 14400 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 120 5700 | 120 | 14400 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 150 3000 | 150 | 18000 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 150 4000 | 150 | 18000 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 150 5700 | 150 | 18000 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 180 3000 | 180 | 19800 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 180 4000 | 180 | 21600 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 180 5700 | 180 | 21600 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 210 3000 | 210 | 23100 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 210 4000 | 210 | 25200 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 210 5700 | 210 | 25200 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 240 3000 | 240 | 26400 | 3000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 240 4000 | 240 | 28800 | 4000K | 120 Degree | ADC | 520 X 670 | 1 |
| LUA5 240 5700 | 240 | 28800 | 5700K | 120 Degree | ADC | 520 X 670 | 1 |

NOMENCLATURE

