

## LED PANEL



### Brief Specification :-

CRI : >80

Power Factor : >0.90

Surge Voltage Protection : 2.5 KV

THD : <15%

IP Rating : IP20

Lifetime : 35,000 Hrs

Abrivations:- RC -RECESSED ,SM - SURFACE MOUNTED

Product Code	Wattage	Lumens	CCT	Beam Angle	Size in mm	Packing
LUA7 24 3000 2X2 RC	24	2160	3000K	120 Degree	600 X 600	1
LUA7 24 4000 2X2 RC	24	2400	4000K	120 Degree	600 X 600	1
LUA7 24 5700 2X2 RC	24	2400	5700K	120 Degree	600 X 600	1
LUA7 36 3000 2X2 RC	36	3240	3000K	120 Degree	600 X 600	1
LUA7 36 4000 2X2 RC	36	3600	4000K	120 Degree	600 X 600	1
LUA7 36 5700 2X2 RC	36	3600	5700K	120 Degree	600 X 600	1
LUA7 45 3000 2X2 RC	45	4050	3000K	120 Degree	600 X 600	1
LUA7 45 4000 2X2 RC	45	4500	4000K	120 Degree	600 X 600	1
LUA7 45 5700 2X2 RC	45	4500	5700K	120 Degree	600 X 600	1
LUA7 15 3000 1X1 RC	15	1350	3000K	120 Degree	300 X 300	1
LUA7 15 4000 1X1 RC	15	1500	4000K	120 Degree	300 X 300	1
LUA7 15 5700 1X1 RC	15	1500	5700K	120 Degree	300 X 300	1
LUA7 18 3000 1X1 RC	18	1620	3000K	120 Degree	300 X 300	1
LUA7 18 4000 1X1 RC	18	1800	4000K	120 Degree	300 X 300	1
LUA7 18 5700 1X1 RC	18	1800	5700K	120 Degree	300 X 300	1
LUA7 24 3000 1X4 RC	24	2160	3000K	120 Degree	300 X 1200	1
LUA7 24 4000 1X4 RC	24	2400	4000K	120 Degree	300 X 1200	1
LUA7 24 5700 1X4 RC	24	2400	5700K	120 Degree	300 X 1200	1
LUA7 36 3000 1X4 RC	36	3240	3000K	120 Degree	300 X 1200	1
LUA7 36 4000 1X4 RC	36	3600	4000K	120 Degree	300 X 1200	1
LUA7 36 5700 1X4 RC	36	3600	5700K	120 Degree	300 X 1200	1
LUA7 45 3000 1X4 RC	45	4050	3000K	120 Degree	300 X 1200	1
LUA7 45 4000 1X4 RC	45	4500	4000K	120 Degree	300 X 1200	1
LUA7 45 5700 1X4 RC	45	4500	5700K	120 Degree	300 X 1200	1
LUA7 24 3000 2X2 SM	24	2160	3000K	120 Degree	600 X 600	1
LUA7 24 4000 2X2 SM	24	2400	4000K	120 Degree	600 X 600	1
LUA7 24 5700 2X2 SM	24	2400	5700K	120 Degree	600 X 600	1

Product Code	Wattage	Lumens	CCT	Beam Angle	Size in mm	Packing
LUA7 36 3000 2X2 SM	36	3240	3000K	120 Degree	600 X 600	1
LUA7 36 4000 2X2 SM	36	3600	4000K	120 Degree	600 X 600	1
LUA7 36 5700 2X2 SM	36	3600	5700K	120 Degree	600 X 600	1
LUA7 45 3000 2X2 SM	45	4050	3000K	120 Degree	600 X 600	1
LUA7 45 4000 2X2 SM	45	4500	4000K	120 Degree	600 X 600	1
LUA7 45 5700 2X2 SM	45	4500	5700K	120 Degree	600 X 600	1
LUA7 15 3000 1X1 SM	15	1350	3000K	120 Degree	300 X 300	1
LUA7 15 4000 1X1 SM	15	1500	4000K	120 Degree	300 X 300	1
LUA7 15 5700 1X1 SM	15	1500	5700K	120 Degree	300 X 300	1
LUA7 18 3000 1X1 SM	18	1620	3000K	120 Degree	300 X 300	1
LUA7 18 4000 1X1 SM	18	1800	4000K	120 Degree	300 X 300	1
LUA7 18 5700 1X1 SM	18	1800	5700K	120 Degree	300 X 300	1
LUA7 24 3000 1X4 SM	24	2160	3000K	120 Degree	300 X 1200	1
LUA7 24 4000 1X4 SM	24	2400	4000K	120 Degree	300 X 1200	1
LUA7 24 5700 1X4 SM	24	2400	5700K	120 Degree	300 X 1200	1
LUA7 36 3000 1X4 SM	36	3240	3000K	120 Degree	300 X 1200	1
LUA7 36 4000 1X4 SM	36	3600	4000K	120 Degree	300 X 1200	1
LUA7 36 5700 1X4 SM	36	3600	5700K	120 Degree	300 X 1200	1
LUA7 45 3000 1X4 SM	45	4050	3000K	120 Degree	300 X 1200	1
LUA7 45 4000 1X4 SM	45	4500	4000K	120 Degree	300 X 1200	1
LUA7 45 5700 1X4 SM	45	4500	5700K	120 Degree	300 X 1200	1

## NOMENCLATURE

