


SOLAR LED STREET LIGHT



Brief Specification :-

CRI : >70
 Power Factor : >0.90
 Surge Voltage Protection : 2.5 - 10 KV
 THD : <15%
 IP Rating : IP66
 Lifetime : 35 ,000 Hrs
 Autonomy : 1 -3 Days

Product Code	Wattage	Lumens	CCT	Body Type	Size in mm	Packing
LUA12 10 3000 18V20W 12V6AH LTH	10	1200	3000K	ADC	310 X 180	1
LUA12 10 5700 18V20W 12V6AH LTH	10	1200	5700K	ADC	310 X 180	1
LUA12 20 3000 18V50W 12V18AH LTH	20	2200	3000K	ADC	310 X 180	1
LUA12 20 5700 18V50W 12V18AH LTH	20	2000	5700K	ADC	310 X 180	1
LUA12 50 3000 18V80W 12V36AH LTH	50	6000	3000K	ADC	420 X 270	1
LUA12 50 5700 18V80W 12V36AH LTH	50	6000	5700K	ADC	420 X 270	1
LUA12 60 3000 18V90W 12V42AH LTH	60	7200	3000K	ADC	420 X 270	1
LUA12 60 5700 18V90W 12V42AH LTH	60	7200	5700K	ADC	420 X 270	1
LUA12 10 3000 18V20W 12V36AH LACD	10	1200	3000K	ADC	310 X 180	1
LUA12 10 5700 18V20W 12V36AH LACD	10	1200	5700K	ADC	310 X 180	1
LUA12 20 3000 18V50W 12V36AH LACD	20	2200	3000K	ADC	310 X 180	1
LUA12 20 5700 18V50W 12V36AH LACD	20	2000	5700K	ADC	310 X 180	1
LUA12 50 3000 18V80W 12V36AH LACD	50	6000	3000K	ADC	420 X 270	1
LUA12 50 5700 18V80W 12V36AH LACD	50	6000	5700K	ADC	420 X 270	1
LUA12 60 3000 18V90W 12V36AH LACD	60	7200	3000K	ADC	420 X 270	1
LUA12 60 5700 18V90W 12V36AH LACD	60	7200	5700K	ADC	420 X 270	1