

LED TUBELIGHT & BATTEN




Brief Specification :-

CRI : >80
 Power Factor : >0.90
 Surge Voltage Protection : 2.5
 THD : <15%
 IP Rating : IP20
 Lifetime : 25 ,000 Hrs
 Abrivations:- BT -BATTEN, RF - RETRO FIT,
 AL - ALUMINIUM BODY, PC -
 POLYCARBONATE

Product Code	Wattage	Lumens	CCT	Beam Angle	Size in mm	Packing
LED RETROFIT TUBE						
LUA6 10 3000 AL RF	10	1000	3000K	120 Degree	600	12
LUA6 10 4000 AL RF	10	1000	4000K	120 Degree	600	12
LUA6 10 5700 AL RF	10	1000	5700K	120 Degree	600	12
LUA6 10 3000 PC RF	10	1000	3000K	120 Degree	600	12
LUA6 10 4000 PC RF	10	1000	4000K	120 Degree	600	12
LUA6 10 5700 PC RF	10	1000	5700K	120 Degree	600	12
LUA6 18 3000 AL RF	18	1800	3000K	120 Degree	1200	12
LUA6 18 4000 AL RF	18	1800	4000K	120 Degree	1200	12
LUA6 18 5700 AL RF	18	1800	5700K	120 Degree	1200	12
LUA6 18 3000 PC RF	18	1800	3000K	120 Degree	1200	12
LUA6 18 4000 PC RF	18	1800	4000K	120 Degree	1200	12
LUA6 18 5700 PC RF	18	1800	5700K	120 Degree	1200	12
LUA6 22 3000 AL RF	22	2200	3000K	120 Degree	1200	12
LUA6 22 4000 AL RF	22	2200	4000K	120 Degree	1200	12
LUA6 22 5700 AL RF	22	2200	5700K	120 Degree	1200	12
LUA6 22 3000 PC RF	22	2200	3000K	120 Degree	1200	12
LUA6 22 4000 PC RF	22	2200	4000K	120 Degree	1200	12
LUA6 22 5700 PC RF	22	2200	5700K	120 Degree	1200	12

LED BATTEN



Product Code	Wattage	Lumens	CCT	Beam Angle	Body Type	Size in mm Dia. X Depth	Packing
LUA6 10 3000 AL BT	10	1000	3000K	120 Degree	AL / PC	600	12
LUA6 10 4000 AL BT	10	1000	4000K	120 Degree	AL / PC	600	12
LUA6 10 5700 AL BT	10	1000	5700K	120 Degree	AL / PC	600	12
LUA6 10 3000 PC BT	10	1000	3000K	120 Degree	AL / PC	600	12
LUA6 10 4000 PC BT	10	1000	4000K	120 Degree	AL / PC	600	12
LUA6 10 5700 PC BT	10	1000	5700K	120 Degree	AL / PC	600	12
LUA6 18 3000 AL BT	18	1800	3000K	120 Degree	AL / PC	1200	12
LUA6 18 4000 AL BT	18	1800	4000K	120 Degree	AL / PC	1200	12
LUA6 18 5700 AL BT	18	1800	5700K	120 Degree	AL / PC	1200	12
LUA6 18 3000 PC BT	18	1800	3000K	120 Degree	AL / PC	1200	12
LUA6 18 4000 PC BT	18	1800	4000K	120 Degree	AL / PC	1200	12
LUA6 18 5700 PC BT	18	1800	5700K	120 Degree	AL / PC	1200	12
LUA6 22 3000 AL BT	22	2200	3000K	120 Degree	AL / PC	1200	12
LUA6 22 4000 AL BT	22	2200	4000K	120 Degree	AL / PC	1200	12
LUA6 22 5700 AL BT	22	2200	5700K	120 Degree	AL / PC	1200	12
LUA6 22 3000 PC BT	22	2200	3000K	120 Degree	AL / PC	1200	12
LUA6 22 4000 PC BT	22	2200	4000K	120 Degree	AL / PC	1200	12
LUA6 22 5700 PC BT	22	2200	5700K	120 Degree	AL / PC	1200	12

NOMENCLATURE

