

LED STREET LIGHT



Brief Specification :-

CRI : >70

Power Factor : >0.90

Surge Voltage Protection : 2.5 - 10 KV

THD : <15%

IP Rating : IP66

Lifetime : 35 ,000 Hrs

Product Code		Wattage	Lumens	CCT	Body Type	Size in mm	Packing
LUA4 10 3000		10	1100	3000K	ADC	310 X 180	1
LUA4 10 4000		10	1200	4000K	ADC	310 X 180	1
LUA4 10 5700		10	1200	5700K	ADC	310 X 180	1
LUA4 20 3000		20	2200	3000K	ADC	310 X 180	1
LUA4 20 4000		20	2400	4000K	ADC	310 X 180	1
LUA4 20 5700		20	2400	5700K	ADC	310 X 180	1
LUA4 50 3000		50	5500	3000K	ADC	420 X 270	1
LUA4 50 4000		50	6000	4000K	ADC	420 X 270	1
LUA4 50 5700		50	6000	5700K	ADC	420 X 270	1
LUA4 60 3000		60	6600	3000K	ADC	420 X 270	1
LUA4 60 4000		60	7200	4000K	ADC	420 X 270	1
LUA4 60 5700		60	7200	5700K	ADC	420 X 270	1
LUA4 90 3000		90	9900	3000K	ADC	420 X 270	1
LUA4 90 4000		90	10800	4000K	ADC	420 X 270	1
LUA4 90 5700		90	10800	5700K	ADC	420 X 270	1
LUA4 120 3000		120	13200	3000K	ADC	420 X 270	1
LUA4 120 4000		120	14400	4000K	ADC	420 X 270	1
LUA4 120 5700		120	14400	5700K	ADC	420 X 270	1

NOMENCLATURE

