

## LED BULB



### Brief Specification :-

CRI : >80  
 Power Factor : >0.90  
 Surge Voltage Protection : 2.5  
 THD : <15%  
 IP Rating : IP20  
 Lifetime : 25 ,000 Hrs

Product Code	Wattage	Lumens	CCT	Beam Angle	Size in mm	Packing
LUA2 07 3000 B22	7	700	3000K	120 Degree	60 X 108	30
LUA2 07 4000 B22	7	700	4000K	120 Degree	60 X 108	30
LUA2 07 5700 B22	7	700	5700K	120 Degree	60 X 108	30
LUA2 07 3000 E27	7	700	3000K	120 Degree	60 X 108	30
LUA2 07 4000 E27	7	700	4000K	120 Degree	60 X 108	30
LUA2 07 5700 E27	7	700	5700K	120 Degree	60 X 108	30
LUA2 09 3000 B22	9	900	3000K	120 Degree	60 X 108	30
LUA2 09 4000 B22	9	900	4000K	120 Degree	60 X 108	30
LUA2 09 5700 B22	9	900	5700K	120 Degree	60 X 108	30
LUA2 09 3000 E27	9	900	3000K	120 Degree	60 X 108	30
LUA2 09 4000 E27	9	900	4000K	120 Degree	60 X 108	30
LUA2 09 5700 E27	9	900	5700K	120 Degree	60 X 108	30
LUA2 12 3000 B22	12	1200	3000K	120 Degree	60 X 108	30
LUA2 12 4000 B22	12	1200	4000K	120 Degree	60 X 108	30
LUA2 12 5700 B22	12	1200	5700K	120 Degree	60 X 108	30
LUA2 12 3000 E27	12	1200	3000K	120 Degree	60 X 108	30
LUA2 12 4000 E27	12	1200	4000K	120 Degree	60 X 108	30
LUA2 12 5700 E27	12	1200	5700K	120 Degree	60 X 108	30

## COLOURFUL LED BULBS

Product Code	Wattage	Body Type	Size in mm	Packing		
LUA2 03 R	3	AL / PC	Standard	30		
LUA2 03 G	3	AL / PC	Standard	30		
LUA2 03 B	3	AL / PC	Standard	30		
LUA2 05 R	5	AL / PC	Standard	30		
LUA2 05 G	5	AL / PC	Standard	30		
LUA2 05 B	5	AL / PC	Standard	30		

## NOMENCLATURE

